

EXTREME DUTY 72 M-AX - Standard and High Flow options available*



72 M-AX at work



(1) Standard Drop Blade Assembly



(2) Optional 4 Blade Assembly.
Inset is close up of blade and dual carrier.



Side View



Hoses and Couplers Standard



Cab View

72 M-AX Performance

- Available for skid steers with standard or high flow auxiliary hydraulics.
- Devours dense vegetation.
- "V Notch" provides a close cut to fell trees.
- Cuts trees up to 10" in diameter – dependent upon type of wood and the vegetation density.
- Heavy 3 blade carrier assembly provides extreme blade speed and cutting force.
- The **optional** dual carrier assembly with 4 reversible blades are 3 times the strength of mild steel. Provides longer-life and improved performance.
- Relief valves protect your motor from pressure spikes and aid in faster shut-down time.
- The 72 M-AX has extreme power and will exceed your expectations.
- **Three year warranty on the structural steel.**

SPECIFICATIONS	(1) Standard 3 Blade Assembly	(2) Optional 4 Blade Assembly
Cutting Width:	72.000	72.000
Overall Width:	75.250	75.250
Overall Length:	84.625	84.625
Cutting Capacity:	10"	10"
Blade Carrier Type:	1.000 Disc - High Strength	(2) .625 Discs - High Strength
Blades:	(3) .625 x 5.000 (High Strength, Updraft)	(4) .625 x 5.188 (High Strength, Flat, Reversible)
Blade Rotation:	Counter Clockwise	Counter Clockwise
Motor Protection:	Pressure Relief, Case Drain	Pressure Relief, Case Drain
Deck Thickness:	.250 One Piece of Formed Steel	
Hydraulic Hose with Protective Wrap:	114.000	
Flat Face Coupling:	Standard	
*Standard Flow GPM option:	23 - 29	23 - 29
*High Flow GPM option:	30 - 40	30 - 40
PSI Min/Max:	3000/4100	3000/4100
Weight:	2,072 lbs.	2,396 lbs.

